

C100 Consumer Solid State Drive (SSD)

Introduction

The C100 series solid state drive is developed from years of experience and expertise on storage technology and flash memory management. This product is specialized for optimization of computer operating systems and offers stable and fast data service by accelerating startup and performance.



Available Model

HS-SSD-C100/120G HS-SSD-C100/240G HS-SSD-C100/480G HS-SSD-C100/960G HS-SSD- C100/1920G

Features and Functions

- High R/W speed
 - SATA 3.0
 - Read speed up to 560 MB/s
- 3D NAND technology
 3D NAND offers the potential for higher capacity, performance, and stability
- Vibration resistant structure Free of mechanical structure, electronic chip control for better data safety
- Slim and portable
 - ➢ 2.5-inch
 - > 7 mm thick





Model name	HS-SSD-C100				
Capacity	120GB	240GB	480GB	960GB	1920GB
Size	2.5 inch				
Max Seq read	550MB/s	550MB/s	550MB/s	560MB/s	560MB/s
MAX Seq Write	420MB/s	450MB/s	470MB/s	500MB/s	520MB/s
Max. random 4K read IOPS	60K	61K	63K	76K	78K
Max. random 4K write IOPS	70K	73K	76K	76K	76K
Power Consumption READ	1.25W	1.34W	1.67W	1.67W	1.67W
Power Consumption WRITE	1.28W	1.32W	1.64W	1.64W	1.64W
Power Consumption IDLE	0.3W	0.32W	0.38W	0.38W	0.38W
Endurance(TBW)	50TB	100TB	200TB	400TB	800TB
NAND FLASH	3D TLC				
Protocol	SATA 6Gb/s				
Form Factor	2.5 inch SATA				
MTBF (Mean Time between Failures)	2,000,000 hours				
Work Temperature	0-70°C				
Warranty	3 years				
TRIM	yes				

Specifications

Note: Performance test is performed in a specific testing environment and Based on ATTO Disk Bench Mark . Any change of computer system, operation system, hardware, software, or functions will influence the test result.

Distributed by

L



Headquarters Rm.01, 21/F, F4 Building, 5th Phase-NO.1 Software Park, Guanshan 1 Rd, East Lake Development Zone, Wuhan, China(430040)