



TS-431XeU-2G	
CPU	AnnapurnaLabs Alpine AL314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor
CPU Architecture	32-bit ARM
Floating Point Unit	Yes
Encryption Engine	Yes
System Memory	2 GB SODIMM DDR3 (1 x 2 GB)
Maximum Memory	8 GB (1 x 8 GB)
Memory Slot	1 x SO-DIMM DDR3
Flash Memory	512MB (Dual boot OS protection)
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	2
10 Gigabit Ethernet Port	1 x 10GbE SFP+
Wake on LAN (WOL)	Yes
Jumbo Frame	Yes
USB 3.2 Gen 1 port	4
Form Factor	1U Rackmount
LED Indicators	HDD 1-4, Status, USB, LAN1-3
Buttons	Power, Reset

Dimensions (HxWxD)	44 × 439 × 291 mm
Weight (Net)	4.15 kg
Weight (Gross)	5.78 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	Open-frame 100W, Input: 100V-240V ~ / 3.5A, 50Hz-60Hz
Power Consumption: HDD Sleep Mode	12.42 W
Power Consumption: Operating Mode, Typical	30.99 W
Fan	System fan: 3 x 40mm, 12VDC
Sound Level	20.3 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	400

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test