

24-Port Gigabit Ethernet Switch

CGS-2400



FEATURES

- Connection speed up to 1000 Mbps
- 24 x 10/100/1000Mbps Auto-Negotiation Ports
- Easy plug & play connection
- Power saving by Link Status & Cable Length

DESCRIPTION

CNet's CGS-2400 Gigabit Ethernet Switch is designed to transfer large files such as voice, music, movies, and large photos in a home or office network. Each port supports up to 2000Mbps of throughput. With CGS-2400, your home or office network is faster and smoother.

SPECIFICATIONS

Model Name	<ul style="list-style-type: none"> CGS-2400
Ports	<ul style="list-style-type: none"> 24 x 10/100/1000 BASE-T TP Copper Ports
Standards	<ul style="list-style-type: none"> IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control for Full-Duplex Operation
Auto-MDIX	<ul style="list-style-type: none"> All TP ports support Auto-MDI/MDI-X Function
LED Indicators	<ul style="list-style-type: none"> POWER Signifies the switch has power LINK//ACT Signifies that connections is made on the Ethernet port. Blinking indicates traffic. SPEED ON signifies 1000Mbps connection. OFF signifies 10/100Mbps connection.
Mode Switch	<ul style="list-style-type: none"> Uplink mode: Port 23 and 24 work as uplink port. Port 1-22 cannot communicate with each other but port 23 and 24. Network Clone mode: Flow control is disabled. Normal mode: Flow control function is enabled.
MAC addresses	<ul style="list-style-type: none"> 8K entries Maximum, Self-Learning
Environment	<ul style="list-style-type: none"> Operating Temperature: 0° ~ 40° C Storage Temperature: -20° ~ 70° C Humidity: 10% ~ 90% Non-condensing
Power Supply	<ul style="list-style-type: none"> Switching Power Adapter, Input: 100-240V
Dimensions	<ul style="list-style-type: none"> 442 x 230 x 44 mm

