

H3C Magic BS218F-HP 18 Ports Gigabit Ethernet

PoE Switch

Release Date:


May, 2023





Product overview

H3C Magic BS218F-HP is a new generation Gigabit unmanaged green PoE switch launched by H3C. It is easy to install, provides a rich set of features, and is widely used in small and medium-sized enterprises, commercial chains, hotels, campuses, and other scenarios.



H3C Magic BS218F-HP Gigabit unmanaged PoE switch

Features and benefits

PoE capable

- The switch is PoE+ capable, delivering a total PoE output of 225 W and a maximum PoE output of 30 W on a single port.
- It uses an advanced PoE chip, ensuring high availability and compatibility.

Multiple working modes

The switch can operate in standard, isolation, aggregation, or clone mode and supports one-key switching of the working mode.

High performance

With a cache sharing architecture, the switch multiplies the available cashing space for each port, greatly enhancing the forwarding performance especially in the event of unexpected and sudden traffic bursts.

High reliability

- Integrated with enterprise-level lightning protection circuit.
- Built with a high-voltage power supply.

Technical specifications

Item	Specification
------	---------------



Dimensions (H × W × D)	44 × 440 × 210mm (1.72 × 17.22 × 9.27 in)	
Dimensions (H X W X D)	44 × 440 × 210mm (1.73 × 17.32 × 8.27 in)	
Ports	16 x 10/100/1000BASE-T copper ports (2 uplink ports)	
	2 × 1000BASE-X SFP ports (uplink ports)	
	Standard	
Operating mode	Isolation	
operating mode	Aggregation	
	Clone	
MAC address entries	8K	
Switching capacity	36 Gbps	
Forwarding capacity	26.8 Mpps	
Packet caching	4 Mb	
Switching mode	Store-and-forward switching	
	PoE+ supported	
PoE+	Supports PoE Power up to 225 W for all PoE ports(16 PoE ports)	
	Supports PoE Power up to 30 W for each PoE port	
Power	100 to 240V AC	
Auto-MDI/MDIX	Yes	
Cooling method	Fan cooling	
Operating temperature/storage temperature	0°C to 40°C (32°F to 104°F)/–40°C to +70°C (–40°F to +158°F)	
Operating humidity/storage humidity	5% to 95% RH, noncondensing	
Certification	CE,RoHS	
MTBF	> 50000 H	
Installation method	Rack-mount by using mounting brackets	

Ordering information

Description	Quantity	Remarks
H3C Magic BS218F-HP Ethernet Switch (16GE+2SFP+PoE, AC)	1	



New H3C Technologies Co., Limited

Beijing Headquarters

Tower 1, LSH Center, 8 Guangshun South Street, Chaoyang

District, Beijing, China

Zip: 100102

Hangzhou Headquarters

Copyright ©2021 New H3C Technologies Co., Limited Reserves all rights

Disclaimer: Though H3C strives to provide accurate information in this document, we cannot guarantee that details do not

H3C reserves the right for the modification of the contents herein without prior notification